

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 08-168243

(43)Date of publication of application : 25.06.1996

(51)Int.Cl.

H02M 3/28

H02M 3/338

(21)Application number : 06-332083

(71)Applicant : YAMAHA CORP

(22)Date of filing : 12.12.1994


(72)Inventor : YOKOYAMA KENJI

(54) SWITCHING POWER SOURCE CIRCUIT

(57)Abstract:

PURPOSE: To provide a switching power source circuit which is reduced in cost and noise and improved in efficiency.

CONSTITUTION: A switching power source circuit is provided with a transformer T in which one end of its primary winding P1 is connected to one terminal B1 of a DC power source, a switching transistor Q1 connected between the other end of the winding P1 and the other terminal B2 of the DC power source, timing circuits 2 and 3 which control the turning on/off of the transistor Q1, and a rectifying and smoothing circuit 4 provided on the secondary side of the transformer T. In addition, a parallel circuit 3 composed of a capacitor Ci which constitutes a current resonance circuit together with the leakage inductance of the transformer T and an inductance element Li which absorbs the electric charges of the capacitor Ci is connected in series with the primary winding P1 of the transformer and a voltage resonance circuit is constituted of a capacitor Cv provided between the collector and emitter of the transistor Q1 and the main inductance of the primary winding of the transistor T.



LEGAL STATUS

[Date of request for examination]

08.08.1996

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

2806283

[Date of registration]

24.07.1998

[Number of appeal against examiner's decision of rejection]

[Date of requesting appeal against examiner's
decision of rejection]

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office